


Cathode ray tube device

Patent number: CN1175077
Publication date: 1998-03-04
Inventor: MASANOBU HONDA (JP); TOSHIO OSE (JP);
KENICHIRO TANIWA (JP)
Applicant: MATSUSHITA ELECTRIC CORP (JP)
Classification:
- International: H01J29/76
- european:
Application number: CN19960114472 19961115
Priority number(s): JP19960227147 19960828


Also published as:

 JP10069863 (/

Report a data error he

Abstract not available for CN1175077
Abstract of corresponding document: **JP10069863**

PROBLEM TO BE SOLVED: To provide a cathode-ray tube device with good convergence by correcting convergence coma as well as correcting green misconvergence at the corner of a screen. **SOLUTION:** For the z-axial magnetic field distribution curve of a secondary distortion coefficient H2 showing the curvature of the deflection-directional magnetic flux density change of the cross section (an x-y cross section) a coil at a right angle to its center axis (a z-axis) in a horizontally deflecting magnetic field generated by a deflecting yoke, a negative minimum value H2a exists near an inlet plane EN specified at the flange portion on the electron gun side of the horizontally deflecting coil and a positive maximum value H2b exists between the inlet plane EN and an outlet plane EX specified at the flange portion on the screen side of the horizontally deflecting coil, a coefficient rh (= $(|H2b| - |H2a|) / |H2b|$), regularized by the absolute value of the positive maximum value H2b, showing a deviation between the absolute value of the negative minimum value H2a and the absolute value of the positive maximum value H2b being -0.30 to 0.19.



Data supplied from the esp@cenet database - Worldwide